

**CASING TECHNICAL DATA SHEET**  
**9.625 x 0.395 J55 Buttress**

Reviewed by: Sr. Quality Engineer  
Approved by: Corporate Director-QEHS

TDS Date (MM/DD/YY)

5-4-26

**PIPE BODY DATA**

Nominal Outside Diameter  
Nominal Wall Thickness  
Remaining Body Wall (RBW)  
Type of Thread  
Grade  
Coupling Type

Label Weight  
Plain End Weight  
Pipe Minimum Yield  
Pipe Maximum Yield  
Pipe Minimum Tensile  
Standard Drift Diameter (min)  
Alternate Drift Diameter (min)  
Pipe Body Plain End Yield  
Pipe Body Internal Yield  
Collapse Pressure - Standard  
Collapse Pressure - High

**CONNECTION DATA**

Coupling Minimum Yield  
Coupling Maximum Yield  
Coupling Minimum Tensile  
Coupling or Joint Outside Diameter (nom)  
Coupling Thread Fracture Strength  
Pipe Thread Fracture Strength  
Pull Out Strength  
Nominal Make-Up Torque or Make-up Torque Range  
Coupling Internal Yield  
Internal Yield of Joint

**WELDED TUBE GENERAL INPUT CRITERIA**

Coupling Color Code  
Coupling Color Code for the Band  
Pipe Color Code Identification  
Additional Color Band (approx. 10' from box end)

Note:

Unit	Imperial	Metric	Unit
in	9.625	244.48	mm
in	0.395	10.03	mm
	87.5%	87.5%	
	Buttress	Buttress	
	J55	J55	
	11th Edition	11th Edition	
	40.00	59.53	
lb/ft	38.97	57.99	kg/m
ksi	55	379	MPa
ksi	80	552	MPa
ksi	75	517	MPa
in	8.679	220.45	mm
in	8.750	222.25	mm
lb	630,000	285,760	kg
psi	3,950	27,230	kPa
psi	2,570	17,720	kPa
psi	N/A	N/A	kPa
ksi	55	379	MPa
ksi	80	552	MPa
ksi	75	517	MPa
in	10.625	269.88	mm
lb	1,318,000	597,830	kg
lb	714,000	323,860	kg
lb	N/A	N/A	kg
ft-lb	N/A	N/A	N-m
psi	6,070	41,850	kPa
psi	3,950	27,230	kPa

	Bright Green
	One White
2" Band(s)	One Bright Green
	N/A

Welded Tube has issued this document for general information only. This does not constitute a warranty, MTR, certificate of compliance, or similar. The content of this technical data sheet shall be reviewed by the user for verification of suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. Welded Tube disclaims any and all expressed or implied warranties of fitness for particular application. Welded Tube has the right to change this data at any time as an improvement of the product or process.

This is an un-controlled document.